

Safety Data Sheet

EPOX-STICK

**AEROCHEM**

Section 1. Identification

Manufacturer

AEROCHEM Inc.
5977 Trans Canada Highway Pointe-Claire, QC
H9R 1C1 Canada
Tel. 514-630-2800
General Information: 1-888-592-5837
Fax 514-630-2828
www.aerochem.ca

Emergency telephone number INFOTRAC® 1-800-535-5053. International call collect: 1-352-323-3500 24 hours/day, 7 days/week.

Product name

Code EPOX-STICK
PAEPOXSTICKA114G

Specific uses

Sealants and adhesives

Section 2. Hazards identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1

GHS label elements

Hazard pictograms



Signal word

Warning!

Hazard statements

Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.

Precautionary statements

Prevention

Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

Not applicable.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

None known.

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

| Ingredient name | % by weight | CAS number |
|---|-------------|------------|
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 10 - 30 | 25068-38-6 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 1 - 5 | 90-72-2 |
| crystalline silica, non-respirable | 0.1 - 1 | 14808-60-7 |

Canada

| Name | CAS number | % |
|---|------------|---------|
| Talc , not containing asbestiform fibres | 14807-96-6 | 30 - 60 |
| glass, oxide, chemicals | 65997-17-3 | 10 - 30 |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 25068-38-6 | 10 - 30 |
| Nepheline syenite | 37244-96-5 | 10 - 30 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | 1 - 5 |
| crystalline silica, non-respirable | 14808-60-7 | 0.1 - 1 |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation

No known significant effects or critical hazards.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Eye contact

Causes serious eye irritation.

Ingestion

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Section 4. First aid measures

| | |
|--|---|
| Inhalation | No specific data. |
| Skin contact | Adverse symptoms may include the following: irritation redness |
| Eye contact | Adverse symptoms may include the following: pain or irritation watering redness |
| Ingestion | No specific data. |
| <u>Indication of immediate medical attention and special treatment needed, if necessary</u> | |
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | No specific treatment. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical No specific fire or explosion hazard.

National Fire Protection Association (U.S.A.)



Hazardous thermal decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

| Ingredient name | CAS # | Exposure limits |
|------------------------------------|------------|---|
| crystalline silica, non-respirable | 14808-60-7 | OSHA PEL (United States, 6/2016). TWA: 50 µg/m³ 8 hours. Form: Respirable dust OSHA PEL Z3 (United States, 6/2016). TWA: 30 mg/m³ / (%SiO ₂ +2) 8 hours. Form: Total dust |

Canada

| Occupational exposure limits | | TWA (8 hours) | | | STEL (15 mins) | | | Ceiling | | | Notations |
|---|------------------------------------|---------------|-------|----------|----------------|-------|-------|---------|-------|-------|-----------|
| Ingredient | List name | ppm | mg/m³ | Other | ppm | mg/m³ | Other | ppm | mg/m³ | Other | |
| Talc, not containing asbestiform fibres | US ACGIH 3/2016 | - | 2 | - | - | - | - | - | - | - | [a] |
| | AB 4/2009 | - | 2 | - | - | - | - | - | - | - | [b] |
| | BC 7/2016 | - | 2 | - | - | - | - | - | - | - | [c] |
| | - | - | - | 0.1 f/cc | - | - | - | - | - | - | - |
| | ON 7/2015 | - | 2 | - | - | - | - | - | - | - | [d] |
| | - | - | - | 2 f/cc | - | - | - | - | - | - | - |
| | QC 1/2014 | - | 3 | - | - | - | - | - | - | - | [e] |
| | SK 7/2013 | - | 2 | - | - | - | - | - | - | - | [f] |
| | US ACGIH 3/2016 | - | 5 | - | - | - | - | - | - | - | [g] |
| | US ACGIH 3/2016 | - | - | 1 f/cc | - | - | - | - | - | - | [h] |
| glass, oxide, chemicals | AB 4/2009 | - | 5 | 1 f/cc | - | - | - | - | - | - | [i] |
| | - | - | 5 | - | - | - | - | - | - | - | [j] |
| | BC 7/2016 | - | 5 | - | - | - | - | - | - | - | [k] |
| | - | - | - | 1 f/cc | - | - | - | - | - | - | - |
| | ON 7/2015 | - | 5 | - | - | - | - | - | - | - | [l] |
| | QC 1/2014 | - | - | 1 f/cc | - | - | - | - | - | - | [m] |
| | - | - | 10 | - | - | - | - | - | - | - | [n] |
| | Nepheline syenite | - | 10 | - | - | - | - | - | - | - | [o] |
| | crystalline silica, non-respirable | - | 0.1 | - | - | - | - | - | - | - | [e] |
| | QC 1/2014 | - | - | - | - | - | - | - | - | - | - |

Form: [a]Respirable fraction [b]Respirable particulate [c]Respirable [d]Respirable fraction. [e]Respirable dust. [f]respirable fraction [g]Inhalable fraction [h]Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination. [i]Fibres [j]Fibres, total particulate [k]Inhalable [l]Inhalable fraction. [m]RESPIRABLE FIBRES (other than respirable asbestos fibres) : Objects, other than respirable asbestos fibres, longer than 5 µm, having a diameter of less than 3 µm and a ratio of length to diameter of more than 3 :1. [n]Total dust. [o]Total dust

Appropriate engineering controls

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Section 9. Physical and chemical properties

Physical state

Solid.

Color

White. Beige. [Light]

Odor

Pungent. Sulfurous. [Strong]

Odor threshold

Not available.

pH

Not applicable.

Melting point

Not available.

Boiling point

Not available.

Flash point

Closed cup: >93.3°C (>199.9°F) [Setaflash.] [Product does not sustain combustion.]

Evaporation rate

Not applicable.

Flammability (solid, gas)

Not available.

Lower and upper explosive (flammable) limits

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

1.95

Solubility

Easily soluble in the following materials: methanol and acetone.
Insoluble in the following materials: cold water and hot water.

Solubility in water

Not applicable.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

Aerosol product

Section 10. Stability and reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

No specific data.

Section 10. Stability and reactivity

Incompatible materials

No specific data.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|------------|----------|
| 2,4,6-tris (dimethylaminomethyl)phenol | LD50 Dermal | Rat | 1280 mg/kg | - |
| | LD50 Oral | Rat | 1200 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|--------------------------|---------|-------|--------------------------|-------------|
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | Eyes - Mild irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 microliters | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |
| 2,4,6-tris (dimethylaminomethyl)phenol | Eyes - Severe irritant | Rabbit | - | 24 hours 50 Micrograms | - |
| | Skin - Mild irritant | Rat | - | 0.025 Milliliters | - |
| | Skin - Severe irritant | Rat | - | 0.25 Milliliters | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 2 milligrams | - |

Sensitization

No specific data.

Mutagenicity

No specific data.

Carcinogenicity

No specific data.

Conclusion/Summary

: This product contains talc in a polymer matrix. Sanding the cured product may release particles containing talc with the polymer and other components of the matrix into the air. The talc contains less than 1% crystalline silica. Appropriate evaluations of the use of the product should be performed to determine if exposure to talc occurs due to handling and use. If such exposures occur, appropriate precautions must be taken to prevent exposure in excess of the OSHA Permissible Exposure Limit (PEL).

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|------------------------------------|------|------|---------------------------------|
| crystalline silica, non-respirable | - | 1 | Known to be a human carcinogen. |

Reproductive toxicity

No specific data.

Teratogenicity

No specific data.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

No specific data.

Specific target organ toxicity (repeated exposure)

No specific data.

Aspiration hazard

No specific data.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact

Causes serious eye irritation.

Inhalation

No known significant effects or critical hazards.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation

No specific data.

Skin contact

Adverse symptoms may include the following:
irritation
redness

Ingestion

No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects

Not available.

Potential delayed effects

Not available.

Long term exposure

Potential immediate effects

Not available.

Potential delayed effects

Not available.

Potential chronic health effects

No specific data.

General

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

| Route | ATE value |
|--------|---------------|
| Oral | 15129.8 mg/kg |
| Dermal | 16138.4 mg/kg |

Section 12. Ecological information

Toxicity

No specific data.

Persistence and degradability

No specific data.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---|--------------------|-----|-----------|
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 2.64 to 3.78 | 31 | low |
| 2,4,6-tris(dimethylaminomethyl)phenol | 0.219 | - | low |

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification

Not applicable.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | IMDG | IATA |
|-------------------------|--------------------|--------------------|-----------------------|----------------|----------------|
| UN Number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| | | | | | |

Section 14. Transport information

| | | | | | |
|----------------------------|-----|-----|-----|-----|-----|
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | - | - | - | - | - |

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

U.S. Federal regulations

TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: zinc sulphide

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)

Not listed

Clean Air Act Section 602 Class I Substances

Not listed

Clean Air Act Section 602 Class II Substances

Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ

Not applicable.

SARA 311/312

Classification

Immediate (acute) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|---|---------|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 10 - 30 | No. | No. | No. | Yes. | No. |
| 2,4,6-tris(dimethylaminomethyl)phenol | 1 - 5 | No. | No. | No. | Yes. | No. |
| crystalline silica, non-respirable | 0.1 - 1 | No. | No. | No. | No. | Yes. |

SARA 313

Section 15. Regulatory information

| | Product name | CAS number | % |
|---------------------------------|---------------|------------|-------|
| Form R - Reporting requirements | zinc sulphide | 1314-98-3 | 1 - 5 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

The following components are listed: TALC; SOAPSTONE; FIBROUS GLASS

New York

None of the components are listed.

New Jersey

The following components are listed: SOAPSTONE; SILICA, QUARTZ; QUARTZ (SiO₂); ZINC compounds

Pennsylvania

The following components are listed: TALC; SOAPSTONE DUST; QUARTZ DUST; QUARTZ; ZINC COMPOUNDS

Minnesota Hazardous Substances

None of the components are listed.

California Prop. 65

| Ingredient name | Cancer | Reproductive | No significant risk level | Maximum acceptable dosage level |
|---|--------------|--------------|---------------------------|---------------------------------|
| Talc , not containing asbestiform fibres crystalline silica, non-respirable | Yes. Yes. | No. No. | - - | - - |

Canada

Canadian lists

Canadian NPRI

The following components are listed: Zinc (and its compounds)

CEPA Toxic substances

None of the components are listed.

Canada inventory

Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

Australia inventory (AICS): Not determined.

China inventory (IECSC): All components are listed or exempted.

Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Korea inventory: All components are listed or exempted.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI): All components are listed or exempted.

Thailand inventory: Not determined.

Turkey inventory: Not determined.

Vietnam inventory: Not determined.

Substances of very high concern

None of the components are listed.

Section 16. Other information

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References

Not available.

Indicates information that has changed from previously issued version.

Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of AEROCHEM. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. AEROCHEM makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by AEROCHEM are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. AEROCHEM assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. AEROCHEM shall in no event be liable for any special, incidental, or consequential damages.