

Safety Data Sheet

WAXY



AEROCHEM

1. Identification

Product identifier	WAXY
Product code	FLWAXY20LT, FLWAXY205LT
Other means of identification	WAXY, liquid. This SDS sheet is not for the product in aerosol format.
Recommended use of the chemical and restrictions on use	Long term rust protection. Not recommended for any other use not detailed on product data sheet or label.
Manufacturer	AEROCHEM Inc. 5977 Trans Canada Highway Pointe-Claire, QC H9R 1C1 Canada General Information: 1-888-592-5837 www.aerochem.ca info@aerochem.ca
Emergency phone number	INFOTRAC®: 1-800-535-5053 International call collect: 1-352-323-3500 24 hours/day, 7 days/week

2. Hazard identification

Summary	FLAMMABLE LIQUID! Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

WHMIS 2015/GHS/OSHA HCS 2012



Flammable liquids (Category 3)
Skin irritation (Category 2)
Specific target organ toxicity, single exposure, Narcotic effects (Category 3)
Aspiration hazard (Category 1)

DANGER

H226: Flammable liquid and vapour
H304: May be fatal if swallowed and enters airways
H315: Causes skin irritation
H336: May cause drowsiness or dizziness
H411: Toxic to aquatic life with long lasting effects
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist, vapours and spray.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye protection.
 P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.
 P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
 P332+313: If skin irritation occurs: Get medical advice or attention.
 P304+340+P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
 P321: Specific treatment (see section 4 of SDS).
 P362+364: Take off contaminated clothing and wash before reuse.
 P370+378: In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
 P391: Collect spillage.
 P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
 P405: Store locked up.
 P501: Dispose of contents and container to an approved waste disposal plant.

Other hazards which do not result in classification

Long-term hazard to the aquatic environment (Category 2)

3. Composition/information on ingredients

Common name	CAS	Weight % content
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	80 - 100 %
Distillates (Petroleum), hydrotreated light	64742-47-8	5 - 10 %
Oxidate	Confidential sol	1 - 5 %
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - 5 %

Note: Oxidate is a Trade Secret with low dermal toxicity. Its oral toxicity and toxicity by inhalation is unknown; however, no adverse effects is anticipated under normal use conditions. The manufacturer withholds the actual concentration range of the ingredients as a trade secret.

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Flush with water for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with plenty of water. Never give anything by mouth if victim is unconscious or convulsing. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause redness and irritation to eyes. May cause dry skin, itching and irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, vertigo, nausea, drowsiness and fatigue. Harmful or fatal if inhaled into the lungs (ingestion/vomiting). Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
Notes to the physician	Apply a symptomatic and supportive treatment. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemicals, water spray, chemical foam, carbon dioxide (CO ₂). Do not use a heavy water jet.
Specific hazards arising from the chemical	Flammable liquid and vapours. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. Product floating on water can travel to an ignition source and spread the fire. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.


6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry into sewers, closed areas and release to the environment. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Ventilate the area well. Remove sources of ignition. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Finish cleaning the contaminated surface by rinsing with soapy water. Dispose via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling	Keep away from heat and open flame. Avoid all sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use in well ventilated area. Do not breathe vapours, mists or aerosols. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep only the quantities necessary for the work being performed in the work area. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Ground or bond large containers. Store tightly closed and in properly labelled containers in a cool, dry and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat. Keep away from freezing.
Storage temperature	0 to 50 °C (32 to 122 °F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	No IDLH value is reported.			
Naphtha (petroleum), hydrotreated heavy (C6-C13)	TWA (8h)	Mist	5 mg/m ³ 175 ppm	ACGIH , RSST Other
Distillates (Petroleum), hydrotreated light	TWA (8h)		200 mg/m ³	ACGIH , BC, ON
Distillates (petroleum), hydrotreated heavy naphthenic	STEL	Mist	10 mg/m ³	RSST
	TWA (8h)	Mist	1 mg/m ³	BC
		Mist	5 mg/m ³	ACGIH , ON, RSST
Appropriate engineering controls	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
Individual protection measures				
Eye	No measures will be necessary. If there is a risk of contact with eyes, wear chemical splash goggles.			
Hands	Wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.			
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear synthetic or a neoprene apron, if necessary, to prevent repeated or prolonged contact with skin. To clean up a spill, if necessary, wear a synthetic polyethylene coveralls such as the Tychem (DuPont) or equivalent coveralls manufactured to provide protection against liquid chemical.			
Respiratory	Respiratory protection is not required for normal use. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.			
Feet	Wear rubber boots to clean up a spill.			
 Apron Goggles Nitrile gloves				

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Tan	Flammability limits	N/Av.
Odour	Solvent odor	Flash point	>58 °C (136.4 °F)
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	No

Freezing point	N/Av.	Vapour density	4.55 (Air = 1)
Boiling point	170°C (338°F)	Relative density	0.89 kg/L (Water = 1)
Solubility	Insoluble in water.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	992.8kPa (7446 mm Hg)	Viscosity	N/Av.
Percent Volatile	50%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available for this product.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Keep away from heat and open flame. Avoid contact with incompatible materials.
Incompatible materials	Strong bases, strong acids, strong oxidizing agents (e.g. chlorine, fluorine, nitric acid, perchloric acid, peroxides, nitrates, chlorates, chromates, permanganates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	Naphtha (petroleum), hydrotreated heavy (C6-C13)	Ingestion >10000 mg/kg Rat LD50 Inhalation >8.5 mg/l/4h Rat LC50 Skin >3200 mg/kg Rabbit LD50
	Distillates (Petroleum), hydrotreated light	Ingestion >5000 mg/kg Rat LD50 Inhalation >10.2 mg/l/4h Rat LC50 Skin 3160 mg/kg Rabbit LD50
	Distillates (petroleum), hydrotreated heavy naphthenic	Ingestion >5000 mg/kg Rat LD50 Inhalation >5 mg/l/4h Rat LC50 Skin >5000 mg/kg Rabbit LD50
	Oxidate	Skin >5000 mg/kg Rabbit LD50
Likely routes of exposure	Skin, eyes, inhalation, ingestion.	
Delayed, immediate and chronic effects	Eye contact	May cause eye irritation. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.
	Skin contact	May cause skin irritation. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.
	Inhalation	May cause respiratory tract irritation. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Prolonged or repeated exposure may cause damages to target organ. The severity of symptoms may vary depending on exposure conditions.
	Ingestion	May cause headaches, nausea, vomiting and weakness. This product contains a mixture of hydrocarbons (CAS no. 64742-52-5 and 64742-47-8) that may cause


	<p>irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, abdominal pain, and central nervous system effects such as headache, dizziness, drowsiness, and generalized weakness. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.</p> <p>Respiratory or skin sensitization Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.</p> <p>IARC/NTP Classification No ingredients listed.</p> <p>Carcinogenicity Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.</p> <p>Mutagenicity Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.</p> <p>Reproductive toxicity Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects.</p> <p>Specific target organ toxicity - single exposure Central nervous system.</p> <p>Specific target organ toxicity - repeated exposure No target organ is listed.</p>
Interactive effects	No information available.
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation (aerosol/mist) of the mixture was calculated to be greater than 5 mg/L/4h. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

12. Ecological information


Ecological toxicity	<p>Fish - Rainbow trout - Salmo gairdneri - fresh water LC50 >1000 mg/L; 96 h (CAS no 64742-47-8)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 >1000 mg/L; 48 h (CAS no 64742-47-8)</p> <p>Green Algae - Selenastrum capricornutum EC50 >1000 mg/L; 72 h (CAS no 64742-47-8)</p> <p>Fish - Rainbow trout - Salmo gairdneri - fresh water LC50 >100 mg/L; 96 h (CAS no Confidential sol)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 >100 mg/L; 48 h (CAS no Confidential Sol)</p> <p>Green Algae - Selenastrum capricornutum EC50 >100 mg/L; 72 h (CAS no Confidential Sol)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 >10000 mg/L; 48 h (CAS no 64742-52-5)</p> <p>Fish - Pimephales promelas - Fresh water LC50 8.2 mg/L; 96 h (CAS no 64742-48-9)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 4.5 mg/L; 48 h (CAS no 64742-48-9)</p>
Persistence	Contains an or many ingredients that may be persistent in aquatic environment.
Degradability	The product is a hydrocarbon mixture in which some ingredients are not readily biodegradable (OECD 301F). Naphtha (petroleum), hydrotreated heavy (C6-C13) (CAS no 64742-48-9) is expected to biodegrade only very slowly in the environment (10% in 28 days, OECD 301D). Distillats légers (pétrole), hydrotraités (CAS no 64742-47-8) are readily biodegradable with a result of >60% in 14 days (OECD 301F). Oxidate is not readily biodegradable with an average biodegradability of 55% in 28 days (OECD 301F). Distillates (petroleum), hydrotreated heavy naphthenic (CAS no 64742-52-5) is not readily biodegradable with an average biodegradability of 31% in 28 days (OECD 301F).
Bioaccumulative potential	The product is a hydrocarbon mixture of which some ingredients have different bioaccumulation potentials. Naphtha (petroleum), hydrotreated heavy (CAS no 64742-48-9) has Log Kow values ranging from 2.1 to 6.5 and Bioconcentration Factor (BCF) of >3000 for the oil mixture. These values indicate a high degree of bioaccumulation. Oxidate has the potential to bioaccumulate according to its high partition coefficient (Log Kow >9.4).
Mobility in soil	The product is a hydrocarbon mixture of which some ingredients can evaporate into the air while others present a medium to low mobility in soil.

Other adverse effects	This chemical does not deplete the ozone layer.
------------------------------	-------------------------------------------------

13. Disposal considerations

 Container	Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Empty containers can be treated (recycled) where there is a recovery program. Organic solvents and wastes residues can be reprocessed (recycle) where there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

14. Transport information

UN Number	UN 1268
UN Proper Shipping Name	PETROLEUM DISTILLATES, N.O.S.
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	Permit required for transportation with proper DANGER placards displayed on vehicle. Exemption available: Not regulated by TDG Canada - art. 1.33; Mode of transportation: rail, sea and road, applicable for Canadian domestic shipments. Quantitative limits: applicable for small container with a capacity =< 450L each.
TDG - Transportation of Dangerous Goods (Canada)	
Transport hazard class(es)	 Class 3
Packing group	III
Emergency response guidebook 2016	128
IMO/IMDG - International Maritime Transport	
Classification	UN 1268. PETROLEUM DISTILLATES, N.O.S. Class 3, PG III. Emergency schedules (EmS-No) F-E, S-E
IATA - International Air Transport Association	
Classification	UN 1268. PETROLEUM DISTILLATES, N.O.S. Class 3, PG III.
These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.	

15. Regulatory information

CANADA					
Common name	CAS	CEPA	DSL	NDSL	NPRI
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9		X		
Distillates (Petroleum), hydrotreated light	64742-47-8	X	X		X
Oxidate	Confidential sol		X		

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5		X	
--------------------------------------------------------	------------	--	---	--

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X								
Distillates (Petroleum), hydrotreated light	64742-47-8	X								
Oxidate	Confidential sol	X								
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	X								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

No ingredients listed.

Other regulations

HMIS	
1	Health
2	Flamability
0	Reactivity
X	Protective Equipment



16. Other information

Date (YYYY-MM-DD)	AEROCHEM Inc. 2020-03-03
Version	04
Other information	<p>REFERENCES:</p> <ul style="list-style-type: none"> - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, https://haz-map.com/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - Database, Institut National de Recherche et de Sécurité, http://www.inrs.fr/accueil/produits/bdd.html

DATE OF FIRST VERSION OF SDS:
2016-02-11.
CHANGES MADE IN THE VERSION 02:
sections 2, 5, 9, 14 and 15.
DATE OF SECOND VERSION OF SDS:
2018-01-16.
CHANGES MADE IN THE VERSION 03:
section 3.
DATE OF THIRD VERSION OF SDS:
2019-08-01.
CHANGES MADE IN THE VERSION 04:
section 1.

TM/MD

ACGIH: American Conference of Governmental Industrial Hygienists
AIHA: American Industrial Hygiene Association
HMIS: Hazardous Materials Identification System
NFPA: National Fire Protection Association
OSHA: Occupational Safety and Health Administration (USA)
NIOSH: National Institute for Occupational Safety and Health
NTP: National Toxicology Program
RSST: Règlement sur la santé et la sécurité du travail (Québec)
GHS: Globally Harmonized System
IARC: International Agency for Research on Cancer
IDLH: Immediately Dangerous to Life or Health
STEL: Short Term Exposure Limit (15 min)
TWA: Time Weighted Averages
WHMIS: Workplace Hazardous Materials Information System

Powered by



A global vision of
prevention

To the best of our knowledge, the information contained herein is accurate. However, neither Preventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.