



Solvent free grease specially conceived for heavy-duty equipment operating under extreme shock loads, high pressures, vibrations.



- **Contain no lead and asphalt base compound**
- **Very adhesive grease that won't run or drip even at high temperature**
- **High concentration of MOLY keeping metal-to-metal wears to minimum**
- **Totally insoluble in bad weather condition, boiling or salt water**
- **Reduces lubrication frequencies**
- **Prevents premature wear on gears and cables**
- **Good transfer from tooth to tooth on open gears in operation**
- **Remarquable stand of pressure, charges and high temperature**
- **Ecological products approved by Agriculture Canada**

Heavy equipments work hard and require special lubrication. An inadequate lubrication of your heavy equipment may cause mechanical breakdown and costly downtime. At AÉROCHEM we have developed our CS-PB grease to insure proper lubrication for extreme conditions even high temperature.

TECHNICAL SPECIFICATION

Very tacky soft grease with molybdenum disulfide "MOLY" and special additives that gives remarkable resistance to water, steam and salt mist. Resist to high charges, impacts, and is usable on open gears at low speed. Prolongs life expectancy of mechanical parts preventing oxidation. Offers exceptional lubricity. Reduce lubrication frequencies. It wont harded or calcinate.

PHYSICAL PROPERTIES

Texture	Adhesive
Color	Black
Base oil @ 40°C	550 cst.
Base oil @ 100°C	150 cst
NLGI	00
BASE	Synthetic
Optimal temperature use	-30°C to +260°C (-22°F to +500°F)
Water washout ASTM-1264, loss	3,5%
TIMKEN load, ASTM D 2509	35 kg
Drop point	200°C (392°F)

CS-PB GREASE COMPATIBILITY CHART

CALCIUM SULFONATE Somewhat compatible*	CALCIUM COMPLEX: Not compatible **
LITHIUM: Fully compatible	BARIUM: Fully compatible
LITHIUM COMPLEX: Fully compatible	SODIUM: Not compatible **
ALUMINIUM COMPLEX: Fully compatible	BENTONE: Fully compatible

*** Mixtures soften, but remains grease like. / ** Mixtures soften severely and turns to oil.**

SIZES

Aerosol	12 x 300g	AECSPB300GDZ
Tonnelet	18 kg	GRCSPB18KG